

# Linear Solenoids


## Frame Solenoids – Standard




Small Frame | Permanent Magnet

STSH-626

### Type



### Force-stroke-diagram (N/mm)



### Description

An integrated permanent magnet is holding the plunger in position 0. To change into a bistable solenoid a spring is necessary.

Extremely small and powerful. Ideal to use with over-current.

Stroke: 6 mm

Holdingforce: 3 N. Weight: 26 g

### Coil Data

Relative Duty Cycle (%)	100	50	25	10
Max. Performance (Watt)	2,5	5	10	25
Max. Duty Cycle (sec.)	∞	60	34	7

### Solenoid Model

Version:

Pull magnet

Pressure Solenoid with spring return

Current:

12 VDC (standard)

24 VDC (standard)

Please ask for other options.

### Special Development On Request

Please contact us for your custom designed part (frame, force, special application, etc.)



**SHENG TENG GmbH**  
 VAT-ID: DE 271 696 661  
 General Manager:  
 Silvio Bruske / Frank Loeffler  
 District Court Munich reg. # HRB185777

Angerbrunnenstraße 11  
 D-85356 Freising  
 GERMANY

Phone: +49-8161-986 44 84  
 Fax: +49-8161-986 44 74  
 eMail: office@shengteng.de

[www.shengteng.de](http://www.shengteng.de)